

	SAFETY DATASHEET	Page : 1/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Ethylene
Chemical description	Ethylene
CAS N°	74-85-1
CE N°	200-815-3
Index N°	601-010-00-3
Registration n°	01-2119462827-27
Chemical formula	C ₂ H ₄

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial and professional Test gas/Calibration gas Chemical reaction / Synthesis Use as a fuel Laboratory use Polymer production Contact supplier for more information on uses
Uses advised against	Consumer use not recommended

1.3. Details of the supplier of the safety data sheet

Company identification	MULTIGAS Route de l'Industrie 102 CH-1564 Domdidier
Phone number	+41 (0) 26 676 94 94
E-mail address	info@multigas.ch

1.4. Emergency telephone numbers

145 (Toxicology Centre Zurich) or +41 (0) 44 251 51 51
 +41 (0) 26 676 94 94 (Multigas)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Flammable gases, Category 1

H220

	SAFETY DATASHEET	Page : 2/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

Gases under pressure : Liquefied gas H280

Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS02

GHS04

GHS07

Signal word

Danger

Hazard statements


H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H336	May cause drowsiness or dizziness

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe gas, vapours
P304+P340+P315	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381	In case of leakage, eliminate all ignition sources
P410+403	Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

None

	SAFETY DATASHEET	Page : 3/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Concentration	Classification
Ethylene	(CAS-No.) 74-85-1 (EC-No.) 200-815-3 (EC Index-No.) 601-010-00-3 (Registration-No.) 01-2119462827-27	<= 100%	Flam. Gas 1, H220 STOT SE 3, H336 Press. Gas (Liq.), H280

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

Contains no other components or impurities which will influence the classification of the product

3.2. Mixtures

Not established

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	See a doctor. Show this safety data sheet to the attending physician
In case of inhalation	In case of inhalation, remove the person from the contaminated area. In case of respiratory arrest, give artificial respiration. See a doctor
In case of skin contact	Remove contaminated clothing and shoes immediately. Wash with soap and plenty of water. Take victim immediately to hospital. See a doctor
In case of eyes contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a doctor
In case of ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. See a doctor

4.2. Most important symptoms and effects, both acute and delayed

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination
Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray or water mist. Dry powder. Carbon dioxide. Foam

	SAFETY DATASHEET	Page : 4/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

Unsuitable extinguishing media

Do not use water jet to extinguish

5.2. Special hazards arising from the substance or mixture

Specific hazards

In case of fire or excessive heat, hazardous combustion products may be produced

Exposure to fire may cause containers to rupture/explode

Hazardous combustion products

In case of fire or excessive heat, hazardous combustion products may be produced such as: carbon monoxide.

5.3. Additional information

Cool endangered receptacles with water spray jet from a protected position

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, spray mists or gases

Provide adequate ventilation

Evacuate personnel to a safe place

Personal protective equipment, see section 8

6.2. Environmental precautions

Try to stop the leak

6.3. Methods and material for containment and cleaning up

Ventilate the area

Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost)

6.4. Reference to other sections

See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes

Avoid breathing vapour or mist

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharge

For precautions, see section 2.2

	SAFETY DATASHEET	Page : 5/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-ventilated place
Content under pressure

7.3. Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components with occupational exposure limits

Component	CAS N°	Exposure value type	Control parameter	Source
Ethylene	74-85-1	TWA	10000 ppm	SUVA: Limit values of exposure to workstations
			15000 mg/m ³	
		OEL	-	SUVA: Limit values of exposure to workstations
			-	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation
Gas detectors should be used when flammable / toxic gases / vapours are likely to be released

8.2.2. Individual protection measures, e.g. personal protective equipment

Eye/face protection

Wear goggles and a face shield when transfilling or breaking transfer connections. Standard EN 166

Skin / hand protection

Wear protective gloves when handling gas cylinders. Standard EN 388- Protective gloves against mechanical hazards Wear cold insulating gloves when transferring or disconnecting transfer lines Standard EN 511 - Insulating gloves against cold Wearing chemical resistant gloves Standard EN 374-Protective gloves against chemicals

For short-term use

Material: Nitrile rubber
Penetration time:> 60 min
Glove thickness: 0.4 mm

For long-term use

Material: Fluoroelastomer
Penetration time:> 480 min

	SAFETY DATASHEET	Page : 6/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

Glove thickness: 0.7 mm

Have appropriate, chemical-resistant protective clothing ready for use in emergencies

Respiratory protection

When the risk assessment shows that the use of respirable respirators is appropriate, use a full face mask with EN 14387 multipurpose cartridge. If the mask is the only means of protection, use a full face respirator. Use NIOSH (US) or CEN (EU) tested and approved equipment

8.2.3. Environmental exposure controls

-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa Gas
- Colour Colourless

Odour No data available

Odour threshold No data available

pH No data available

Melting point / Freezing point -169°C

Boiling point -103°C

Flash point -100°C (closed cup)

Evaporation rate No data available

Flammability (solid, gas) Extremely flammable gas

Explosive limits 2.7 – 36%

Vapour pressure [20°C] 35 bar

Vapour pressure [50°C] No data available

Vapour density No data available

Relative density, liquid (water=1) 0.57

Relative density, gas (air=1) 0.97

Water solubility 130 mg/l

Partition coefficient 1.13

n-octanol/water (Log Kow)

Auto-ignition temperature 440°C

Decomposition temperature No data available

Viscosity No data available

Explosive properties No data available

Oxidising properties No data available

	SAFETY DATASHEET	Page : 7/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

9.2. Other information

Molar mass	28 g/mol
Critical temperature [°C]	9.5°C
Relative vapour density	0.97

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

Can form explosive mixture with air
May react violently with oxidants

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking
May decompose violently at high temperature and/or pressure or in the presence of a catalyst

10.5. Incompatible materials

Strong oxidizers, carbon tetrachloride, chlorine, copper, vinyl compounds
For additional information on compatibility refer to ISO 11114


10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Chemical safety assessment

Acute toxicity	Toxicological effects not expected from this product if occupational exposure limit values are not exceeded
Skin corrosion/irritation	No data available
Serious eye damage/irritation	No data available
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	No data available

	SAFETY DATASHEET	Page : 8/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

Carcinogenicity	No data available
Reproductive toxicity	No data available
STOT-single exposure – Target organ(s)	May cause drowsiness or dizziness. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Central nervous system
STOT-repeated exposure	No data available
Ingestion hazard	No data available

SECTION 12: Ecological information

12.1. Toxicity

Assessment	Classification criteria are not met
-------------------	-------------------------------------

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

PBT / vPvB assessment is not available because the chemical safety assessment is not required / is not conducted


12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product	Must not be released into the atmosphere Burn in a chemical incinerator equipped with an afterburner and scrubber Return to the supplier the product not consumed in its original container
Contaminated container	Eliminate as unused product Contact the supplier if instructions are needed
OMoD Code	16 05 04 Gases in pressure containers containing dangerous substances

	SAFETY DATASHEET	Page : 9/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

SECTION 14: Transport information

14.1. UN number

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
1962	1962	1962

14.2. UN proper shipping name

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
Ethylene	Ethylene	Ethylene

14.3. Transport hazard class(es)

Labelling



ADR/RID
IMDG
IATA

2.1 : Flammable gases

14.4. Packing group

ADR/RID
IMDG
IATA

Not established

14.5. Environmental hazards

ADR/RID

None

IMDG

None

ICAO-TI / IATA-DGR

None

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	SAFETY DATASHEET	Page : 10/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

This safety data sheet complies with the requirements of Regulation (CE) No. 1907/2006

15.2. Chemical safety assessment

A CSA has been carried out


SECTION 16: Other information

Indication of changes	Revised safety data sheet in accordance with commission regulation (EU) No 2015/830
Abbreviations and acronyms	<p>ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road</p> <p>CAS : Chemical Abstract Service number (USA)</p> <p>CLP : Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008</p> <p>CSA : Chemical Safety Assessment</p> <p>EIGA : European Industrial Gases Association</p> <p>EINECS : European Inventory of Existing Commercial Chemical Substances</p> <p>EN : European Standard</p> <p>ATE : Acute Toxicity Estimate</p> <p>IATA : International Air Transport Association</p> <p>IMDG Code : International Maritime Dangerous Goods Code</p> <p>LC50 : Lethal Concentration to 50 % of a test population</p> <p>OMoD : Swiss Ordinance on the movement of waste</p> <p>PBT : Persistent, Bioaccumulative and Toxic</p> <p>PPE: Personal Protection Equipment</p> <p>REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006</p> <p>RID : Regulations concerning the international carriage of dangerous goods by rail</p> <p>RMM : Risk Management Measures</p> <p>STOT-SE : Specific Target Organ Toxicity - Single Exposure</p> <p>UN : United Nations</p> <p>vPvB : Very Persistent and Very Bioaccumulative</p> <p>WGK: Water Hazards Class</p>

Full text of H, EUH and P statements used in sections 2 and 3

Hazard statements

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H336	May cause drowsiness or dizziness

	SAFETY DATASHEET	Page : 11/11
		Revised edition n° : 10.0
		Revision date : 08/2018
Ethylene		MTG055A

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260	Do not breathe gas, vapours
P304+P340+P315	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381	In case of leakage, eliminate all ignition sources
P410+403	Protect from sunlight. Store in a well-ventilated place

Disclaimer of liability

Details given in this document have been prepared based on the most available reliable documents and are believed to be correct at the time of going to press

They do not claim to be exhaustive and should be considered as a guide