

Page: 1/11

Revised edition n°: 10.0

Revision date: 11/2020

MTGxxx

R449A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

R449A (DuPont™ Opteon® XP40) Trade name

Refrigerant mixture HFC-HFO (1,1,1,2-Tetrafluoroethane, 2,3,3,3-**Chemical description**

Tetrafluoropropene, Pentafluoroethane, Difluoromethane)

CAS N°

CE N° Index N° Registration n°

Chemical formula $(C_2H_2F_4, C_3H_2F_4, C_2HF_5, CH_2F_2)$

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial and professional

Test gas/Calibration gas

Use for manufacture of electronic/photovoltaic components

Use as refrigerant Laboratory use

Contact supplier for more information on uses

Uses advised against Consumer use not recommended

1.3. Details of the supplier of the safety data sheet

MULTIGAS

Company identification Route de l'Industrie 102

CH-1564 Domdidier

Phone number +41 (0) 26 676 94 94

E-mail address info@multigas.ch

1.4. Emergency telephone numbers

(Toxicology Centre Zurich) or +41 (0) 44 251 51 51

+41 (0) 26 676 94 94 (Multigas)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]



Page : 2/11

Revised edition n°: 10.0

Revision date: 11/2020

MTGxxx

R449A

Physical hazards

Gases under pressure : Liquefied gas

H280

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

 \Diamond

GHS04

Signal word Warning

Hazard statements

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P410+403 Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name | Product identifier | Concentration | Classification |
|---|--|---------------|--|
| 1,1,1,2-Tetrafluoroethane (R134A) | (CAS-No.) 811-97-2 (EC-No.) 212-377-0 (EC Index-No.) (Registration-No.) 01-2119459374-33 | 25.7 % | Press. Gas (Liq.), H280 |
| 2,3,3,3- Tetrafluoropropene (R1234yf) | (CAS-No.) 754-12-1 (EC-No.) 468-710-7 (EC Index-No.) (Registration-No.) 01-0000019665-61 | 25.3 % | Flam. Gas 1, H220 Press. Gas (Liq.), H280 |
| Pentafluoroethane (R125) | (CAS-No.) 354-33-6 (EC-No.) 206-557-8 (EC Index-No.) (Registration-No.) 01-2119485636-25 | 24.7 % | Press. Gas (Liq.), H280 |
| Difluoromethane (R32) | (CAS-No.) 75-10-5 (EC-No.) 200-839-4 (EC Index-No.) (Registration-No.) 01-2119471312-47 | 24.3 % | Flam. Gas 1, H220 Press. Gas (Liq.), H280 |



Page : 3/11

Revised edition n°: 10.0 Revision date: 11/2020

MTGxxx

R449A

For the complete H-sentences texts mentioned in that chapter, refer to Section 16 Contains no other components or impurities which will influence the classification of the product

3.2. Mixtures

Not established

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice See a doctor. Show this safety data sheet to the attending physician

In case of inhalation In case of inhalation, remove the person from the contaminated area. In

case of respiratory arrest, give artificial respiration. See a doctor

In case of skin contact Frostbite should be treated like thermal burns: Immediate, abundant and

prolonged washing with water. Consult a doctor

In case of eyes contact Immediate washing, abundant and prolonged with water. If irritation

persists, consult a doctor

In case of ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Rinse mouth with water. See a doctor

4.2. Most important symptoms and effects, both acute and delayed

May cause asphyxiation at high concentrations. Symptoms may include loss of consciousness or motor skills. The victim may not be aware of the

asphyxia

Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

Do not give adrenaline or similar drugs

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray or water mist. Dry powder. Carbon dioxide. Foam

Unsuitable extinguishing media Do not use water jet

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire or excessive heat, hazardous combustion products may be

produced

Exposure to fire may cause containers to rupture/explode

Hazardous combustion products In case of fire or excessive heat, hazardous combustion products may be

produced such as : carbonyl fluoride, carbon monoxide, hydrogen fluoride



Page : 4/11

Revised edition n°: 10.0

Revision date: 11/2020

MTGxxx

R449A

5.3. Additional information

Cool endangered receptacles with water spray jet from a protected position

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, spray mists or gases

Provide adequate ventilation

Evacuate personnel to a safe place

Personal protective equipment, see section 8

6.2. Environmental precautions

-

6.3. Methods and material for containment and cleaning up

Ventilate the area

6.4. Reference to other sections

See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes

Avoid breathing vapours or mist

Keep away from sources of ignition - No smoking

Take measures to avoid the accumulation of electrostatic charges

For precautions, see section 2.2

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-

ventilated place

Content under pressure

7.3. Specific end use(s)

None



Page : 5/11

Revised edition n°: 10.0 Revision date: 11/2020

MTGxxx

R449A

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components with occupational exposure limits

| Component | CAS N° | Exposure value type | Control parameter | Source |
|---|----------|---------------------|-------------------------|--|
| 1,1,1,2-Tetrafluoroethane (R134A) | 811-97-2 | TWA | 1000 ppm | SUVA: Limit values of |
| | | | 4 240 mg/m ³ | exposure to workstations |
| | | OEL | 200 ppm | SUVA: Limit values of exposure to workstations |
| | | | 1'080 mg/m ³ | |
| 2,3,3,3- Tetrafluoropropene (R1234yf) | 754-12-1 | TWA | - | No limit value of exposure to workstations |
| | | | - | |
| | | OEL | - | |
| | | | - | |
| Pentafluoroethane (R125) | 354-33-6 | TWA | - | No limit value of exposure to workstations |
| | | | - | |
| | | OEL | - | |
| | | | - | |
| Difluoromethane (R32) | 75-10-5 | TWA | - | No limit value of exposure to workstations |
| | | | - | |
| | | OEL | - | |
| | | | - | |

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation

Gas detectors should be used when flammable / toxic gases / vapours are likely to be released

8.2.2. Individual protection measures, e.g. personal protective equipment

Eye/face protection Wear goggles and a face shield when transfilling or breaking transfer

connections. Standard EN 166

Skin / hand protection Wear protective gloves when handling gas cylinders Standard EN 388-

Protective gloves against mechanical hazards



Page : 6/11

Revised edition n°: 10.0 Revision date: 11/2020

MTGxxx

R449A

The selected protective gloves have to satisfy the specifications of EU Directive 89/686 / EEC and the standard EN 374 derived from it

For short-term use

Material: Fluoroelastomer Penetration time:> 480 min Glove thickness: 0.7 mm

For long-term use
Material: Fluoroelastomer
Penetration time:> 480 min

Have appropriate, chemical-resistant protective clothing ready for use in

emergencies

Respiratory protection Self-contained breathing apparatus (SCBA) or positive pressure air mask

Glove thickness: 0.7 mm

must be used in oxygenated atmospheres. Standard EN 137 - Self-

contained compressed air device with a full face mask

8.2.3. Environmental exposure controls

-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C /

Gas

101.3kPa

• Colour Colourless

Odour No data available
Odour threshold No data available
pH No data available
Melting point / Freezing point No data available

Boiling point -46°C

Flash point

Evaporation rate

No data available

No data available

Flammability (solid, gas)

No data available

Explosive limits

No data available

Vapour pressure [20°C] 11.1 bar Vapour pressure [50°C] 23.5 bar

Vapour density No data available

Relative density, liquid (water=1) 1.11 Relative density, gas (air=1) 3.0

Water solubility No data available



Page : 7/11

Revised edition n°: 10.0

Revision date: 11/2020

R449A

MTGxxx

Partition coefficient

No data available

n-octanol/water (Log Kow)

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableViscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Molar mass 87.2 g/mol Critical temperature [°C] 81.5°C

Relative vapour density

Gas/vapour heavier than air. May accumulate in confined spaces,

particularly at or below ground level

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

May react violently with oxidants

May form an explosive mixture with air

10.4. Conditions to avoid

Keep away from heat and sources of ignition. Avoid contact with flames

and red metal surfaces. Do not smoke

10.5. Incompatible materials

Alkaline and alkaline earth metals, Strong oxidizers, Finely divided metals For more information on compatibility, refer to ISO 11114

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information



Page: 8/11

Revised edition n°: 10.0 Revision date: 11/2020

MTGxxx

R449A

11.1. Chemical safety assessment

Acute toxicity

No toxicological effects expected with this product if exposure limit values

are not exceeded

Skin corrosion/irritationNo data availableSerious eye damage/irritationNo data availableRespiratory or skin sensitisationNo data availableGerm cell mutagenicityNo data availableCarcinogenicityNo data availableReproductive toxicityNo data available

STOT-single exposure – Target

organ(s)

No data available

STOT-repeated exposure No data available
Ingestion hazard No data available

SECTION 12: Ecological information

12.1. Toxicity

Assessment Not very harmful for fish

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

PBT / vPvB assessment is not available because the chemical safety assessment is not required / is not conducted

12.6. Other adverse effects

Contains fluorinated greenhouse gases

When discharged in large quantities may contribute to the greenhouse effect

SECTION 13: Disposal considerations



Page : 9/11

Revised edition n°: 10.0

Revision date: 11/2020

MTGxxx

R449A

13.1. Waste treatment methods

Product Must not be released into the atmosphere

Burn in a chemical incinerator equipped with an afterburner and scrubber Return to the supplier the product not consumed in its original container

Contaminated container Eliminate as unused product

Contact the supplier if instructions are needed

OMoD Code 14 06 01

Solvent, refrigerant and aerosol propellant or organic foam wastes:

Chlorofluorocarbons, HCFCs, HFCs

SECTION 14: Transport information

14.1. UN number

| Transport par road/rail ADR / RID | Transport by sea IMDG | Transport by air IATA |
|--------------------------------------|--------------------------|-----------------------|
| 1078 | 1078 | 1078 |

14.2. UN proper shipping name

| Transport par road/rail ADR / RID | Transport by sea IMDG | Transport by air IATA |
|---|---|--|
| REFRIGERANT GAS ; N.O.S. (REFRIGERANT GAS R 449A) | REFRIGERANT GAS ; N.O.S. (REFRIGERANT GAS R 449A) | REFRIGERANT GAS ; N.O.S. (REFRIGERANT GAS R 449A) |

14.3. Transport hazard class(es)

Labelling



ADR/RID IMDG IATA

2.2 : Non-flammable, non-toxic gases

14.4. Packing group

ADR/RID IMDG IATA

Not established

14.5. Environmental hazards

ADR/RID None
IMDG None
ICAO-TI / IATA-DGR None



Page : 10/11

Revised edition n°: 10.0 Revision date: 11/2020

MTGxxx

R449A

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (CE) No. 1907/2006

15.2. Chemical safety assessment

A CSA has not been made yet

SECTION 16: Other information

Indication of changes Revised safety data sheet in accordance with commission regulation (EU)

No 2015/830

Abbreviations and acronyms ADR: European Agreement concerning the International Carriage

of Dangerous Goods by Road

CAS: Chemical Abstract Service number (USA)

CLP : Classification Labelling Packaging Regulation; Regulation

(EC) No 1272/2008

CSA: Chemical Safety Assessment

EIGA: European Industrial Gases Association

EINECS: European Inventory of Existing Commercial Chemical

Substances

EN: European Standard
ATE: Acute Toxicity Estimate

IATA: International Air Transport Association

IMDG Code: International Maritime Dangerous Goods Code
LC50: Lethal Concentration to 50 % of a test population
OMoD: Swiss Ordinance on the movement of waste

PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protection Equipment

REACH: Registration, Evaluation, Authorisation and Restriction of

Chemicals Regulation (EC) No 1907/2006

RID: Regulations concerning the international carriage of

dangerous goods by rail



Page : 11/11

Revised edition n°: 10.0

Revision date: 11/2020

MTGxxx

R449A

RMM: Risk Management Measures

STOT-SE: Specific Target Organ Toxicity - Single Exposure

UN: United Nations

vPvB: Very Persistent and Very Bioaccumulative

WGK: Water Hazards Class

Full text of H, EUH and P statements used in sections 2 and 3

Hazard statements

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P410+403 Protect from sunlight. Store in a well-ventilated place

Disclaimer of liability Details given in this document have been prepared based on the most

available reliable documents and are believed to be correct at the time of

going to press

They do not claim to be exhaustive and should be considered as a guide