

Page: 1/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

R454A (DuPont™ Opteon® XL40) Trade name

R454A

Refrigerant mixture HFC-HFO (2,3,3,3-Tetrafluoropropene, **Chemical description**

Difluoromethane)

CAS N°

CE N° Index N° Registration n°

Chemical formula $(CH_2F_2, C_3H_2F_4)$

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Industrial and professional

Test gas/Calibration gas

Use for manufacture of electronic/photovoltaic components

Use as refrigerant Laboratory use

Contact supplier for more information on uses

Uses advised against Consumer use not recommended

1.3. Details of the supplier of the safety data sheet

MULTIGAS

Company identification Route de l'Industrie 102

CH-1564 Domdidier

Phone number +41 (0) 26 676 94 94

E-mail address info@multigas.ch

1.4. Emergency telephone numbers

(Toxicology Centre Zurich) or +41 (0) 44 251 51 51

+41 (0) 26 676 94 94 (Multigas)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable gases, Category 1



Page: 2/11

Revised edition n°: 10.0

Revision date: 08/2019

MTGxxx

R454A

Gases under pressure: Liquefied gas

H280

For the complete H-sentences texts mentioned in that chapter, refer to Section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





GHS02 Danger GHS04

Signal word

Hazard statements

H220

Extremely flammable gas

H280

Contains gas under pressure; may explode if heated

Precautionary statements

P210

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P377 P381

Leaking gas fire: Do not extinguish, unless leak can be stopped safely Eliminate all ignition sources if safe to do so

P410+403 Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Concentration	Classification
2,3,3,3-Tetrafluoropropene (R1234yf)	(CAS-No.) 754-12-1 (EC-No.) 468-710-7 (EC Index-No.) (Registration-No.) 01-0000019665-61	63 – 67% %	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Difluoromethane (R32)	(CAS-No.) 75-10-5 (EC-No.) 200-839-4 (EC Index-No.) (Registration-No.) 01-2119471312-47	33 - 37%	Flam. Gas 1, H220 Press. Gas (Liq.), H280



Page : 3/11

Revised edition n°: 10.0

Revision date: 08/2019

R454A

MTGxxx

3.2. Mixtures

Not established

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice See a doctor. Show this safety data sheet to the attending physician

In case of inhalation In case of inhalation, remove the person from the contaminated area. In

case of respiratory arrest, give artificial respiration. See a doctor

In case of skin contact Frostbite should be treated like thermal burns: Immediate, abundant and

prolonged washing with water. Consult a doctor

In case of eyes contact Immediate washing, abundant and prolonged with water. If irritation

persists, consult a doctor

In case of ingestionDo NOT induce vomiting. Never give anything by mouth to an unconscious

person. Rinse mouth with water. See a doctor

4.2. Most important symptoms and effects, both acute and delayed

May cause asphyxiation at high concentrations. Symptoms may include loss of consciousness or motor skills. The victim may not be aware of the

asphyxia

Refer to section 11

4.3. Indication of any immediate medical attention and special treatment needed

Do not give adrenaline or similar drugs

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray or water mist. Dry powder. Carbon dioxide. Foam

Unsuitable extinguishing media Do not use water jet

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire or excessive heat, hazardous combustion products may be

produced

Exposure to fire may cause containers to rupture/explode

Hazardous combustion products In case of fire or excessive heat, hazardous combustion products may be

produced such as: carbonyl fluoride, carbon monoxide, hydrogen fluoride

5.3. Additional information

Cool endangered receptacles with water spray jet from a protected position



Page : 4/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

R454A

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, spray mists or gases

Provide adequate ventilation

Evacuate personnel to a safe place

Personal protective equipment, see section 8

6.2. Environmental precautions

-

6.3. Methods and material for containment and cleaning up

Ventilate the area

6.4. Reference to other sections

See also sections 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes

Avoid breathing vapours or mist

Keep away from sources of ignition - No smoking

Take measures to avoid the accumulation of electrostatic charges

For precautions, see section 2.2

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-

ventilated place

Content under pressure

7.3. Specific end use(s)

None



Page : 5/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

R454A

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Components with occupational exposure limits

Component	CAS N°	Exposure value type	Control parameter	Source
2,3,3,3- Tetrafluoropropene (R1234yf)		TWA	-	No limit value of exposure to workstations
	754-12-1		-	
	754-12-1	OEL	-	
			-	
Difluoromethane (R32)		TWA	-	No limit value of exposure to workstations
	75 40 5		-	
	75-10-5	OEL	-	
			-	

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation

Gas detectors should be used when flammable / toxic gases / vapours are likely to be released

8.2.2. Individual protection measures, e.g. personal protective equipment

Eye/face protection Wear goggles and a face shield when transfilling or breaking transfer

connections. Standard EN 166

Skin / hand protection Wear protective gloves when handling gas cylinders Standard EN 388-

Protective gloves against mechanical hazards

The selected protective gloves have to satisfy the specifications of EU

Directive 89/686 / EEC and the standard EN 374 derived from it

For short-term use

Material: Fluoroelastomer Penetration time:> 480 min Glove thickness: 0.7 mm

For long-term use

Material: Fluoroelastomer Penetration time:> 480 min Glove thickness: 0.7 mm

Have appropriate, chemical-resistant protective clothing ready for use in

emergencies

Respiratory protectionSelf-contained breathing apparatus (SCBA) or positive pressure air mask must be used in oxygenated atmospheres. Standard EN 137 - Self-

must be used in oxygenated atmospheres. Standard EN 137

contained compressed air device with a full face mask



Page : 6/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

R454A

8.2.3. Environmental exposure controls

-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C /

Gas

Colour

101.3kPa

Colourless

Odour
Odour threshold

No data available
No data available

pH

No data available

Melting point / Freezing point

No data available

Boiling point

-48.3°C

Flash point

No data available

Evaporation rate

No data available

Flammability (solid, gas)

Flammable

Explosive limits

8 – 15 %

Vapour pressure [20°C]

11.8 bar

Vapour pressure [50°C]

24.4 bar

Vapour density

No data available

Relative density, liquid (water=1)

1

Relative density, gas (air=1)

2.8

Water solubility

No data available

Partition coefficient

No data available

n-octanol/water (Log Kow)

No data available

Auto-ignition temperature Decomposition temperature

No data available

Viscosity

No data available

Explosive properties

No data available

Oxidising properties

No data available

9.2. Other information

Molar mass

80.47 g/mol

Critical temperature [°C]

82°C

Relative vapour density

Gas/vapour heavier than air. May accumulate in confined spaces,

particularly at or below ground level



Page : 7/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

R454A

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

May react violently with oxidants

May form an explosive mixture with air

10.4. Conditions to avoid

Keep away from heat and sources of ignition. Avoid contact with flames

and red metal surfaces. Do not smoke

10.5. Incompatible materials

Air, oxidizers, finely divided metal powders, strong oxidizers For more information on compatibility, refer to ISO 11114

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Chemical safety assessment

Acute toxicity

No toxicological effects expected with this product if exposure limit values

are not exceeded

Skin corrosion/irritation

Serious eye damage/irritation

Respiratory or skin sensitisation

No data available

STOT-single exposure – Target

organ(s)

No data available

STOT-repeated exposure No data available
Ingestion hazard No data available



Page : 8/11

Revised edition n°: 10.0

Revision date: 08/2019

MTGxxx

R454A

SECTION 12: Ecological information

12.1. Toxicity

Assessment The classification criteria are not met

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

PBT / vPvB assessment is not available because the chemical safety

assessment is not required / is not conducted

12.6. Other adverse effects

Contains fluorinated greenhouse gases

When discharged in large quantities may contribute to the greenhouse

effect

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Must not be released into the atmosphere

Burn in a chemical incinerator equipped with an afterburner and scrubber

Return to the supplier the product not consumed in its original container

Contaminated container Dispose of as unused product

Contact the supplier if instructions are required

OMoD Code 14 06 01

Solvent, refrigerant and aerosol propellant or organic foam wastes:

Chlorofluorocarbons, HCFCs, HFCs

SECTION 14: Transport information

14.1. UN number

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
3161	3161	3161



Page : 9/11

Revised edition n°: 10.0

Revision date: 08/2019

MTGxxx

R454A

14.2. UN proper shipping name

Transport par road/rail ADR / RID	Transport by sea IMDG	Transport by air IATA
LIQUEFIED GAS, FLAMMABLE, N.O.S.	LIQUEFIED GAS, FLAMMABLE, N.O.S.	LIQUEFIED GAS, FLAMMABLE, N.O.S.
(2,3,3,3-Tetrafluoropropene, Difluoromethane) R454A	(2,3,3,3-Tetrafluoropropene, Difluoromethane) R454A	(2,3,3,3-Tetrafluoropropene, Difluoromethane) R454A

14.3. Transport hazard class(es)

Labelling

ADR/RID

IATA

IMDG

14.4. Packing group

ADR/RID

IMDG IATA Not established

2.1 Flammable gases

14.5. Environmental hazards

ADR/RID None
IMDG None
ICAO-TI / IATA-DGR None

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (CE) No. 1907/2006

15.2. Chemical safety assessment

A CSA has not been made yet



Page : 10/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

R454A

SECTION 16: Other information

Indication of changes Revised safety data sheet in accordance with commission regulation (EU)

No 2015/830

Abbreviations and acronyms ADR: European Agreement concerning the International Carriage

of Dangerous Goods by Road

CAS: Chemical Abstract Service number (USA)

CLP: Classification Labelling Packaging Regulation; Regulation

(EC) No 1272/2008

CSA: Chemical Safety Assessment

EIGA: European Industrial Gases Association

EINECS: European Inventory of Existing Commercial Chemical

Substances

EN: European Standard
ATE: Acute Toxicity Estimate

IATA: International Air Transport Association

IMDG Code: International Maritime Dangerous Goods Code
LC50: Lethal Concentration to 50 % of a test population
OMoD: Swiss Ordinance on the movement of waste

PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protection Equipment

REACH: Registration, Evaluation, Authorisation and Restriction of

Chemicals Regulation (EC) No 1907/2006

RID: Regulations concerning the international carriage of

dangerous goods by rail

RMM: Risk Management Measures

STOT-SE: Specific Target Organ Toxicity - Single Exposure

UN: United Nations

vPvB: Very Persistent and Very Bioaccumulative

WGK: Water Hazards Class

Full text of H, EUH and P statements used in sections 2 and 3

Hazard statements

H220 Extremely flammable gas

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 Eliminate all ignition sources if safe to do so

P410+403 Protect from sunlight. Store in a well-ventilated place



R454A

Page : 11/11

Revised edition n°: 10.0 Revision date: 08/2019

MTGxxx

Disclaimer of liability

Details given in this document have been prepared based on the most available reliable documents and are believed to be correct at the time of going to press

They do not claim to be exhaustive and should be considered as a guide